

[\[kwkang, jkim\]@ai.kaist.ac.kr](mailto:{kwkang, jkim}@ai.kaist.ac.kr)

Handwritten Hangul Recognition by Dynamic Lattice Search with Structural Constraints

Kyung-Won Kang^o Jin-Hyung Kim
Dept. of EECS, KAIST

, DP

SERI-DB

가

1.

가 (1).

, Hidden Markov Model

[8].

가

(2).

subgraph isomorphism

가 (‘+’ ‘|’),

가 , , 2

가 가



1.

가 [7]. 가

가

가

가

2 (random graph)

3

4

Interactive

Activation Model (IAM)

[5].

2.

[8]

가 1

가

Wickens

가

[6].

(redundancy)


가

가

가

가

(word superiority effect)



2.



3. Random graph

가

가

(3).

, vertex

arc

, vertex

arc

(X:


, G:

, M: X


G

).

$$\arg \max_{(M,G)} P_M(G | X) ? \arg \max_{(M,G)} P_M(X | G)P(G)$$



4.



5. 6

가

가

NP-complete

가

가

가

가

(5).

, best-first

search

(candidate pruning technique)

3.

가

가

4

6

6

가


가

가

가

2

‘산’



6.

가 , 가
가 , 'ㄱ' 'ㄴ'

(dynamic programming matching)
ROI(region of interest)

7

DP matching (6),
best-first search

(fuzzy) (model triggering), 가

ROI bounding box ROI
가 가

가 Best-first search
2

'ㄱ' 가
'ㄱ' 가
2 'ㄱ', 'ㄴ' 가
1 'ㄱ' 가

가


n

17

3.2.

Subgraph isomorphism

(subgraph)



7.

2


1

MODEL 'ㄱ'
 TRIGGERED_BY 'ㅡ'
 VERIFIED_BY ' / '
 RELATION RIGHT_CLOCKWISE

MODEL 'ㄷ'
 TRIGGERED_BY model 'G'
 VERIFIED_BY 'ㅡ'
 RELATION DOWN_CNT_CLOCKWISE WITH 2nd PRIMITIVE
 SUP_RELATION PARALLEL WITH 1st PRIMITIVE



8.



9.

Subgraph isomorphism

$O(M \times S \times C)$

(M:

, S:

, C:

4.

),

(feature-directed

520

matching)

M S

DB SERI-DB

가

[8]

200 set, 104,000

1 set, 520

3.3.

,

(1).

가 가

가 , 가

90%

가

2

(8).

가

0.4 %

(topological constraint).

가

(positional

10 11

constraint).

(noise constraint). Topological

'ㅁ' 가

constraint

가

subgraph isomorphism

ROI

ROI

가

(9).

가

Science 1811), Springer, May 2000

[8]. H. Y. Kim and J. Kim, "Hierarchical Random Graph Representation of Handwritten Characters and its Application to Hangul Recognition," Pattern Recognition, Vol. 34, No. 2, 2000

가

	6671.3	747.2
	91.2 %	90.8 %

1.

[8]

5.

[1]. Jayanta Basak and Sankar K. Pal, "PsyCOP – A Psychologically Motivated Connectionist System for Object Perception," IEEE Trans. Neural Networks, Vol. 6, No. 6, pp. 1337-1354, 1995

[2]. Ethem Alpaydin, "Selective Attention for Handwritten Digit Recognition," Advances in Neural Information Processing Systems, Vol. 8, pp. 771-777, The MIT Press, 1996

[3]. Pierre Van De Laar et al., "Task-Dependent Learning of Attention," Neural Networks, Vol. 10, No. 6, pp. 981-992, 1997

[4]. Ruggero Milanese et al., "Integration of Bottom-Up and Top-Down Cues for Visual Attention Using Non-Linear Relaxation," Proc. IEEE Conf. Computer Vision and Pattern Recognition, 1994

[5]. M. Cote, E. Lecolinet, M. Cheriet, and C. Y. Suen, "Automatic Reading of Cursive Scripts Using a Reading Model and Perceptual Concepts," International Journal of Document Analysis and Recognition, No. 1, 1998

[6]. C. D. Wickens, Engineering Psychology and Human Performance, 2nd Ed., Harper Collins Publishers, 1992

[7]. C. S. Park and S. Y. Bang, "Modeling Character Superiority Effect in Korean Characters by Using IAM, Biologically Motivated Computer Vision (Lecture Notes in Computer



10.



11.